

# Safety data sheet

## according to 1907/2006/EC, Article 31



Printing date 28.10.2016

Version number 4

Revision: 28.10.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **TREMCO JS562 Black B (TR)**

MSDS code: D-T-JS562BLKBTR

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Hardening agent/ Curing agent

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

tremco illbruck Ltd  
Coupland Road, Hindley Green, Wigan, WN2 4HT  
Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410  
msds@tremco-illbruck.com

##### Further information obtainable from:

tremco illbruck Ltd  
Coupland Road, Hindley Green, Wigan, WN2 4HT  
T: +44 (0) 1942251400, F: +44 (0) 1942251410  
www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

#### 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times please contact your national poisoning centre.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1B	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 1B	H360FD	May damage fertility. May damage the unborn child.
STOT SE 3	H335	May cause respiratory irritation.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms



GHS05 GHS07 GHS08

##### Signal word Danger

##### Contains:

3-aminopropyltriethoxysilane  
tetraethyl silicate  
Silicic acid (H<sub>4</sub>SiO<sub>4</sub>), tetraethyl ester, reaction products with bis(acetyloxy)dibutylstannane

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31



Printing date 28.10.2016

Version number 4

Revision: 28.10.2016

**Trade name: TREMCO JS562 Black B (TR)**

(Contd. of page 1)

- **Hazard statements**

- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H360FD May damage fertility. May damage the unborn child.
- H335 May cause respiratory irritation.

- **Precautionary statements**

- P260 Do not breathe vapours.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P201 Obtain special instructions before use.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a doctor.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- **Supplemental information:**

Restricted to professional users.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with non-hazardous additions.

- **Dangerous components:**

CAS: 78-10-4 EINECS: 201-083-8 Reg.nr.: 01-2119496195-28-xxxx	tetraethyl silicate Flam. Liq. 3, H226; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	30- <50%
CAS: 919-30-2 EINECS: 213-048-4 Reg.nr.: 01-2119480479-24-xxxx	3-aminopropyltriethoxysilane Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317	10- <20%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol Flam. Liq. 2, H225	1- <5%
CAS: 93925-42-9 EC number: 300-344-4 Reg.nr.: 01-2119560586-30-xxxx	Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dibutylstannane Flam. Liq. 3, H226; Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; Aquatic Chronic 3, H412	0.1- <1%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 28.10.2016

Version number 4

Revision: 28.10.2016

**Trade name: TREMCO JS562 Black B (TR)**

(Contd. of page 2)

## SECTION 4: First aid measures

### • 4.1 Description of first aid measures

#### • **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out of danger area and lay down.

#### • **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

#### • **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### • **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

#### • **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

### • 4.2 Most important symptoms and effects, both acute and delayed

Causes burns.

Harmful by inhalation.

Irritating to respiratory system.

May cause an allergic skin reaction.

#### • **Information for doctor:** No further relevant information available.

#### • **Hazards** No further relevant information available.

### • 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### • 5.1 Extinguishing media

#### • **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

#### • **For safety reasons unsuitable extinguishing agents:** Water with full jet

### • 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NOx)

methanol

### • 5.3 Advice for firefighters

#### • **Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

## SECTION 6: Accidental release measures

### • 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

### • 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

### • 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31



Printing date 28.10.2016

Version number 4

Revision: 28.10.2016

**Trade name: TREMCO JS562 Black B (TR)**

(Contd. of page 3)

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Keep receptacles tightly sealed.

Avoid contact with the eyes and skin.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

- **Information about storage in one common storage facility:** Protect from heat and direct sunlight.

- **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

#### 78-10-4 tetraethyl silicate

OEL Short-term value: 340 mg/m<sup>3</sup>, 40 ppmLong-term value: 170 mg/m<sup>3</sup>, 20 ppm

#### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

- **Additional Occupational Exposure Limit Values for possible hazards during processing:**

While curing the following substances are formed and released by a reaction with atmospheric humidity:

Ethanol

- **Additional information:**

The lists valid during the making were used as basis.

EH40/2005 Workplace Exposure Limits (2nd edition, 2011)

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

Use only in well-ventilated areas.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31



Printing date 28.10.2016

Version number 4

Revision: 28.10.2016

**Trade name: TREMCO JS562 Black B (TR)**

(Contd. of page 4)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Butyl rubber, BR

Neoprene gloves

PVC gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Pasty

Colour: Black

- **Odour:** Uncharacteristic.

- **pH-value:** Alkaline

- **Flash point:** >100 °C

- **Danger of explosion:** Product does not present an explosion hazard.

- **Density at 20 °C:** 1.06 g/cm<sup>3</sup>

- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

- **Solvent content:**

Organic solvents: 1.3 %

VOC (EU) 1.3 %

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31



Printing date 28.10.2016

Version number 4

Revision: 28.10.2016

**Trade name: TREMCO JS562 Black B (TR)**

(Contd. of page 5)

- **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** Stable
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with water.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Ethanol  
Beginning at approx. 150 °C small amounts of formaldehyde are formed by an oxidative decomposition.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

#### 78-10-4 tetraethyl silicate

Oral	LD50	6270 mg/kg (rat)
Dermal	LD50	5878 mg/kg (rabbit)

#### 919-30-2 3-aminopropyltriethoxysilane

Oral	LD50	1780 mg/kg (rat)
Dermal	LD50	4000 mg/kg (rabbit)

#### 93925-42-9 Silicic acid (H<sub>4</sub>SiO<sub>4</sub>), tetraethyl ester, reaction products with bis(acetyloxy) dibutylstannane

Oral	LD50	1000 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
May damage fertility. May damage the unborn child.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31



Printing date 28.10.2016

Version number 4

Revision: 28.10.2016

Trade name: TREMCO JS562 Black B (TR)

(Contd. of page 6)

- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** Moderately / partly biodegradable
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Must not reach sewage water or drainage ditch undiluted or unneutralised.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Disposal must be made according to official regulations.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste disposal key:** UK (WM3) : HP5 HP8 HP10 HP13

#### • European waste catalogue

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
-----------	--

- **Uncleaned packaging:**
- **Recommendation:**  
Dispose of packaging according to regulations on the disposal of packagings.  
Packagings that may not be cleansed are to be disposed of in the same manner as the product.  
Non contaminated packagings may be recycled.

### SECTION 14: Transport information

- |                                       |  |
|---------------------------------------|--|
| • <b>14.1 UN-Number</b>               |  |
| • <b>ADR, IMDG, IATA</b>              | UN3267   |
| • <b>14.2 UN proper shipping name</b> |  |
| • <b>ADR</b>                          | 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3-aminopropyltriethoxysilane) |
| • <b>IMDG, IATA</b>                   | CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3-aminopropyltriethoxysilane)      |

(Contd. on page 8)

GB



# Safety data sheet

## according to 1907/2006/EC, Article 31



Printing date 28.10.2016

Version number 4

Revision: 28.10.2016

**Trade name: TREMCO JS562 Black B (TR)**

(Contd. of page 7)

- **14.3 Transport hazard class(es)**

- **ADR, IMDG, IATA**



- **Class**

8 Corrosive substances.

- **Label**

8

- **14.4 Packing group**

- **ADR, IMDG, IATA**

III

- **14.5 Environmental hazards:**

- **Marine pollutant:**

No

- **14.6 Special precautions for user**

Warning: Corrosive substances.

- **EMS Number:**

F-A,S-B

- **Segregation groups**

Alkalis

- **Stowage Category**

A

- **Stowage Code**

SW2 Clear of living quarters.

- **Segregation Code**

SG35 Stow "separated from" acids.

- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

- **Transport/Additional information:**

- **ADR**

- **Limited quantities (LQ)**

5L

- **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

- **UN "Model Regulation":**

UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3-AMINOPROPYLTRIETHOXYSILANE), 8, III

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **National regulations:**

- **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

(Contd. on page 9)

GB



# Safety data sheet

## according to 1907/2006/EC, Article 31



Printing date 28.10.2016

Version number 4

Revision: 28.10.2016

**Trade name: TREMCO JS562 Black B (TR)**

(Contd. of page 8)

Employment restrictions concerning pregnant and lactating women must be observed.

- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57** Not applicable.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

#### · **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Muta. 2: Germ cell mutagenicity – Category 2
- Repr. 1B: Reproductive toxicity – Category 1B
- STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- **\* Data compared to the previous version altered.**